

## Preflight Checklist – Cirrus SR20

### Cabin:

- Check Hobbs and Record
- CAPS Safety Pin - In
- Egress Hammer - In Place
- Fire Extinguisher - In Place
- Ignition Off - Key Removed
- All Switches – Off
- Turn Coord. Power – Normal
- Park Brake – As Desired
- Alternate Air, Alternate Static – Normal
- Aux. Vacuum – As desired

### **Battery Master ON**

- Fuel Gages – Check
- Fuel Selector Least Full Tank
- Lower Flaps 100%
- Vac & Oil Lights – On
- Annunciator lights - Test
- Lights – Check All
- Pitot Heat – Check as needed

### **Master OFF**

### Fuel and Oil:

- Sample left wing sumps
- Visually check fuel quantity
- Sample Gascolator
- Fuel cap – Secure
- Sample right wing sumps
- Visually check fuel quantity
- Fuel cap – Secure
- Check oil >6, <8
- Dip stick – Secure
- Door – Secure

### Left Fuselage:

- Com 1 Antenna (top)
- Wing/Fuselage fairing
- Com 2 Antenna (bottom)
- Baggage door – Secure
- Static port
- Parachute cover

### Empennage:

- Stabilizer leading edge
- Elevator counterweight
- Elevator hinges & nuts
- Freedom of movement
- Security
- Remove tail tiedown
- Rudder condition
- Rudder hinges & nuts
- VOR antennas
- Elevator hinges & nuts
- Elevator counterweight
- Freedom of movement
- Security
- Stabilizer leading edge

### Look forward:

- General appearance

### Inspect underside of Fuselage:

- Damage
- Antennas

### Right Fuselage:

- Static port
- Wing/Fuselage fairing

### Right Wing:

- Flap & hinges – Secure
- Aileron hinges – Secure
- Aileron freedom of movement
- Wing tip
- Position/Strobe Lights
- Fuel vent
- Leading edge
- Stall strips
- Stall warning port – Clear
- Gear fairing, tire, brakes
- Remove chocks/tiedown
- Cabin air vent – Clear

### Nose:

- Cowling – Secure
- Exhaust – Secure
- Nose gear, tire – Secure
- Cowl openings – Clear
- Alternator belt – Secure
- Prop blades – nicks, etc.
- Spinner – Secure
- Landing light – Secure
- Cowling – Secure
- Oil door – Closed & Secure
- External power door – Secure
- Exhaust – Secure

### Left Wing:

- Cabin air vent – Clear
- Remove chocks/tiedown
- Gear fairing, tire, brakes
- Stall strips
- Leading edge
- Fuel vent
- Pitot tube – Secure
- Position/Strobe Lights
- Wing tip
- Aileron freedom of movement
- Aileron hinges – Secure
- Flap hinges - Secure

